



CONSTRUCTION SERIES

BUILT FOR STRENGTH

When you need strength and value, the Trailtech Construction series trailers deliver it to you. This series is built to work using a channel iron main frame and tubing crossmembers, and axles that can bear the load.



SPECIFICATIONS

Features	CELR270-18	CELR270 - 20
GVWR	16100 Lbs	16100 Lbs
GAWR (Per Axle)	7000 Lbs	7000 Lbs
Tare Weight (approx.)	2359 lb	2492 lb
Main Frame	6" Channel Iron ASTM A36/44W	6" Channel Iron ASTM A36/44W
Crossmembers	3" x 2" x .125" Tubing	3" x 2" x .125" Tubing
Axles	(2) 7000 lb Electric Braking	(2) 7000 lb Electric Braking
Suspension	5 Leaf Slipper Spring	5 Leaf Slipper Spring
Hitch	Adjustable 2 5/16 inch Ball Coupler	Adjustable 2 5/16 inch Ball Coupler
Jack	8000 lb Drop Foot	8000 lb Drop Foot
Overall Width	102 inches	102 inches
Fenders	Teardrop Fenders	Teardrop Fenders
Inside Fender Width	82.5 inches	82.5 inches
Deck	#1 Kiln Dried Canadian Spruce	#1 Kiln Dried Canadian Spruce
Deck Height	25.25 inches	25.25 inches
Dovetail and Flip Up Ramps	Standard	Standard
Tires (Radial)	ST235/80R16 Load Range E	ST235/80R16 Load Range E
Lights & Wiring	LED c/w Fully Protected Arctic Wiring	LED c/w Fully Protected Arctic Wiring

All models have the following standard features: LED Lights and White spoke rims w/chrome centers.

FEATURES

Spare Tire Carrier

All CEL models have available an optional spare tire, rim & carrier. This allows you to have a spare right on the trailer.

HD 8000# Top Crank Jack

The heavy duty top crank drop leg jack is bolted to the trailer and is easily removeable.

Fender Guards

The fender guard protects against the unexpected and will keep your fenders looking good as new for years to come. This is all done without sacrificing payload space.

Dovetail and Flip-up Ramps

All CEL models are available with Dovetail and Flip Up Ramps, and when loading heavier equipment the extra support of the flip up ramps will meet your needs.

Adjustable Ball Coupler

Hooking up a Construction series trailer is now easier than ever using the adjustable ball coupler to raise or lower the height.

OPTIONS

Spare tire and rim

Available on:

CELR270 18' and CELR270 20'

