



DUMP SERIES

HAULING... SIMPLIFIED

The Dump series include a range of models, all designed to meet your specific needs. Slide in ramps make these trailers ideal for loading and hauling your equipment, and store conveniently under the trailer when not in use. The two-way tailgate features a rear double door and spreader gate, allowing for fast unloading of your materials, or a more controlled flow if you prefer. The versatility and convenience of these trailers give you maximum control and the ability to use the product as a handy dump trailer or a flat deck trailer with complete ease.

SPECIFICATIONS

Features	L270HD PH	L270HD GN	L370HD PH	L370HD GN	L280XHD PH
GVWR	16100 Lbs	16100 Lbs	20990 Lbs	20990 Lbs	18400 Lbs
GAWR (Per Axle)	7000 Lbs	7000 Lbs	7000 Lbs	7000 Lbs	8000 Lbs
Tare Weight (approx.)	4540 Lbs	5010 Lbs	5670 Lbs	6140 Lbs	5045 Lbs
Main Frame	W8 @ 10" I-Beam A992/A572-50	W8 @ 10" I-Beam A992/A572-50	W10 @ 12" I-Beam A992/A572-50	W10 @ 12" I-Beam A992/A572-50	W8 @ 10" I-Beam A992/A572-50
Floor Material	3/16" Plate	3/16" Plate	10ga Plate	10ga Plate	3/16" Plate
Sides	10ga Plate	10ga Plate	10ga Plate	10ga Plate	10ga Plate
Ramps	Slide in Loading Ramps	Slide in Loading Ramps	Slide in Loading Ramps	Slide in Loading Ramps	Slide in Loading Ramps
Tailgate	Double Rear Door	Double Rear Door	Two Way	Two Way	Double Rear Door
Box Size	82" W x 12' L x 18" H and 82" W x 14' L x 18" H	82" W x 14' L x 18" H	82" W x 16' L x 18" H	82" W x 16' L x 18" H	81.75" W x 14' L x 18" H
Jack	12000 lb Drop Foot	Double 12,000 lb	Double 12,000 lb	Double 12,000 lb	12000 lb Drop Foot
Hitch	2 5/16 Adjustable Ball Coupler	Gooseneck c/w 2 5/16" Adjustable Ball Coupler	Adjustable Lunette Eye	Gooseneck c/w 2 5/16" Adjustable Ball Coupler	HD 2 5/16 Adjustable Ball Coupler
Axles	(2) 7000 lb Electric Braking	(2) 7000 lb Electric Braking	(3) 7000 lb Electric Braking	(3) 7000 lb Electric Braking	(2) 8000 lb Electric Braking
Suspension	Torsion	Torsion	Torsion	Torsion	Torsion
Box Support	Full Length Formed Sills Running Length of the Box	Full Length Formed Sills Running Length of the Box	Full Length Formed Sills Running Length of the Box	Full Length Formed Sills Running Length of the Box	Full Length Formed Sills Running Length of the Box

Features	L270HD PH	L270HD GN	L370HD PH	L370HD GN	L280XHD PH
Tires	ST235/80R16 Load Range E	ST235/80R16 Load Range E	ST235/80R16 Load Range E	ST235/80R16 Load Range E	ST235/85R16 Load Range G
Lights & Wiring	LED c/w Fully Protected Arctic Wiring	LED c/w Fully Protected Arctic Wiring	LED c/w Fully Protected Arctic Wiring	LED c/w Fully Protected Arctic Wiring	LED c/w Fully Protected Arctic Wiring

Legend for Model Abbreviations

GN - Gooseneck

PH - Pintle Hitch

FEATURES

Electric/Hydraulic Power Pack

Two way electric/hydraulic power pack with 10' hand held, gives control and safety when unloading, ensuring that a variety of equipment can be accommodated.

Scissor Hoist

The heavy duty high lift hoist provides stability, strength, and optimal dumping angle.

Adjustable Coupling & HD Jack

The adjustable coupling and HD dropleg jack allows for choice of coupling, ease of hook up and ability to tow level loads.

Jeep Style Fenders

The heavy duty jeep style checker plate fenders are designed for long lasting durability and strength.

Unibody Dump Box

Designed for the gravel industry, the dump box provides lower deck height, cleaner flow, and increased stability.

OPTIONS

The L270HD PH model is also available with Slipper Spring Suspension in place of the Torsion Suspension.

