



LEISURE SERIES

MAKING LEISURE EASY

Our lineup of small Utility trailers are perfect for all of those jobs that a large trailer is not required for. Hauling all of your lawn & garden equipment from site to site is done perfectly with this line of trailers. Standard features such as side stake pockets allow easy load securement at nearly any point along the trailer. Underneath the 3500 lb axle and 15" radial tires ensure that these trailers can handle the highway or back roads and keep on rolling.



SPECIFICATIONS

| Features | L135LT-10' | L135LT-12' | BT135-510 | BT135-610 | UT135-8ST | UT135-8HT |
|----------------------------|--|--|---|---|---|---|
| GVWR | 2998 Lbs | 2998 Lbs | 2998 Lbs | 2998 Lbs | 2998 Lbs | 2998 Lbs |
| GAWR (Per Axle) | 2998 Lbs | 2998 Lbs | 2998 Lbs | 2998 Lbs | 2998 Lbs | 2998 Lbs |
| Tare Weight | 695 lb | 750 lb | 827 lb | 904 lb | 639 lb | 669 lb |
| Main Frame | 1.5 x 1.5 x .188 Angle Iron ASTM A36/44W | 1.5 x 1.5 x .188 Angle Iron ASTM A36/44W | 3" x 2" x .125 Tubing ASTM A36/44W | 3" x 2" x .125 Tubing ASTM A36/44W | 3" x 2" x .125 Tubing ASTM A36/44W | 3" x 2" x .125 Tubing ASTM A36/44W |
| Crossmembers | 1.5 x 1.5 x .125 Structural Tubing | 1.5 x 1.5 x .125 Structural Tubing | 1.5 x 1.5 x .125 Structural Tubing | 1.5 x 1.5 x .125 Structural Tubing | 1.5 x 1.5 x .125 Structural Tubing | 1.5 x 1.5 x .125 Structural Tubing |
| Axles | 1-3500 lb Idler | 1-3500 lb Idler | 1-3500 lb Idler | 1-3500 lb Idler | 1-3500 lb Idler | 1-3500 lb Idler |
| Suspension | 4 Leaf Double Eye | 4 Leaf Double Eye | 4 Leaf Double Eye | 4 Leaf Double Eye | 4 Leaf Double Eye | 4 Leaf Double Eye |
| Tilt Deck | Standard | Standard | Standard | Standard | --- | --- |
| Coupler (Moulded) | 2" | 2" | 2" | 2" | 2" | 2" |
| Deck Width | 72" | 72" | 60" | 72" | 48" | 48" |
| Tires | ST205/75R15 Load Range D | ST205/75R15 Load Range D | ST205/75R15 Load Range D | ST205/75R15 Load Range D | ST205/75R15 Load Range D | ST205/75R15 Load Range D |
| Lights & Wiring | LED c/w Fully Protected Arctic Wiring | LED c/w Fully Protected Arctic Wiring | LED c/w Fully Protected Arctic Wiring | LED c/w Fully Protected Arctic Wiring | LED c/w Fully Protected Arctic Wiring | LED c/w Fully Protected Arctic Wiring |

All models have the following standard features: LED Lights and White spoke rims w/chrome centers

All BT Models have the following standard features: 12" High Formed Sides and Front and White Spoke Rims, Plywood Deck

All UT Models have the following standard features: Fold Down Endgate c/w Latches and 16" High Sides and Front, White Spoke Rims

Legend for Model Abbreviations

LT - Light Tilt

BT - Box Tilt

UT - Utility Trailer

ST - Standard Tailgate (16")

HT - High Tailgate (48")

FEATURES

LED Lighting

LED lighting, which allows for faster response time and brighter lights for safety, is standard on all models.

4' Landscape Tailgate

The UT Series Optional 4' landscape tailgate allows for loading of small equipment in a safe stable manner.

Rims & Tires

Standard on the Leisure series are 15" rims and ST205/75R15 Load Range D Radial Tires.

Tilting Deck

The tilting deck makes for easy loading and unloading of all types of equipment from garden tractors to golf carts.

