



SPECIFICATIONS

Features	L135T-12	L135-12	L270T-20	L270DT-18	L270DT-20	L370DT-24	L370T-24
GVWR	2998 Lbs	2998 Lbs	16100 Lbs	16100 Lbs	16100 Lbs	24150 Lbs	24150 Lbs
GAWR (Per Axle)	2998 Lbs	2998 Lbs	7000 Lbs	7000 Lbs	7000 Lbs	7000 Lbs	7000 Lbs
Tare Weight (approx.)	1113 Lbs	1113 Lbs	3173 Lbs	2876 Lbs	3026 Lbs	3770 Lbs	4173 Lbs
Main Frame	4" x 2" x .125" Tubing 4.76# Per Foot ASTM A36/44W4" x 2" x .125" Tubing 4.76# Per Foot 44000KSI	4" x 2" x .125" Tubing 4.76# Per Foot ASTM A36/44W	8" x 2" x .188" Tubing 13.78# Per Foot ASTM A36/44W				
Crossmembers	1.5" x 1.5" x .125" Tubing on 24" Centers	1.5" x 1.5" x .125" Tubing on 24" Centers	3" x 2" x .125 Tubing on 19.2" Centers				
Axles	(1) 3500 lb Idler	(1) 3500 lb Idler	(2) 7000 lb Electric Braking	(2) 7000 lb Electric Braking	(2) 7000 lb Electric Braking	(3) 7000 lb Electric Braking	(3) 7000 lb Electric Braking
Suspension	4 Leaf Slipper Spring	4 Leaf Slipper Spring	Torsion	Torsion	Torsion	Torsion	Torsion
Hitch	2" Molded Ball Coupler	2" Molded Ball Coupler	Adjustable 2 5/16 Ball Coupler	Adjustable 2 5/16 Ball Coupler	Adjustable 2 5/16 Ball Coupler	Adjustable Lunette Eye	Adjustable Lunette Eye
Jack	3000 lb Top Crank	3000 lb Top Crank	12000 lb Drop Foot				
Overall Width	102"	102"	102"	102"	102"	102"	102"

Features	L135T-12	L135-12	L270T-20	L270DT-18	L270DT-20	L370DT-24	L370T-24
Fenders	16 GA	16 GA	1/8" Checkerplate Jeep Style				
Inside Fender Width	79.5"	79.5"	82.5"	82.5"	82.5"	82.5"	82.5"
Slide in Ramps		Standard					
Deck Height	17"	17"	24"	24"	24"	24"	24"
Dovetail and Ramps				Standard	Standard	Standard	
Deck	#1 Kiln Dried Canadian Spruce						
Tires (Radial)	ST205/75R15 Load Range D	ST205/75R15 Load Range D	ST235/80R16 Load Range E				
Lights & Wiring	LED c/w Fully Protected Arctic Wiring	LED c/w Fully Protected Arctic Wiring	LED c/w Fully Protected Arctic Wiring	LED c/w Fully Protected Arctic Wiring	LED c/w Fully Protected Arctic Wiring	LED c/w Fully Protected Arctic Wiring	LED c/w Fully Protected Arctic Wiring

Optional

Black MOD Rims c/w Black Center Caps & Black Nuts

Series 07 Aluminum Rimsc/w Center Caps & Acorn Nuts

Paint - Standard Colours Charcoal Grey, Midnight Blue, Construction Yellow

Other colours available upon request

Legend for Model Abbreviations

T - Tilt Deck

DT - Dovetail

FEATURES

Dove Tail & Ramps

The unique pivot dovetail flip up ramps allow even hard to load equipment to be loaded and unloaded with ease. The ramps are adjustable side to side, ensuring that a variety of equipment can be accommodated.

Tool Box c/w Locking Lid

All tandem axle Premier trailers feature a tool box c/w locking lid in the hitch area for your convenience.

Adjustable Ball Coupler / Pinte

Hooking up the Premier trailer is now easier than ever with the adjustable ball coupler /pintle. This feature allows you to raise or lower the height of the coupler to match you vehicle's hitch height. Just another example of Trailtech ingenuity.

Tilt Deck

The tilt deck measures 82.5" between fenders, allowing for those wider loads. Simply drive your unit up onto the deck, and when you are over center the deck will start to go into transport mode on its own.

Fender Guard

Fender guards are steel plates added to the rear of the fenders to protect from accidental bumps into the fenders when loading.

OPTIONS

	T'	О,		<i>-</i> .
Snara	IIΓΔ	RIM	ana	(arriar
Sparc	111 (,	1 / 11 1 1	arru	Carrier

Available on:

All Models

All L270 and L370 Models listed are available with optional Slipper Spring Suspension in place of the Torsion Suspension.

