



TRANSPORT SERIES

THE TRANSPORT SPECIALISTS

Loading and transporting your straight cut headers is now easy and simple. Whether traveling long distances or simply moving your equipment around the farm, these transports are built to last.



SPECIFICATIONS

Features	HT6000	HT7000	HTM	HT21000SB	H1000
New Feature	---	---	---	---	---
Main Frame	8" x 6" Structural Tubing	8" x 6" Structural Tubing	8" x 8" Structural Tubing	Dual 8" x 6" Structural Tubing	---
Length	29.5'	38'	---	---	---
Header Brackets	Dual Arms	Quad Adjustable Arms	Quad Adjustable Arms	Slanted Bed	---
Axle(s)	Single 6000 lb	Single 7000 lb	Single and Tandem	Tridem	---
Suspension	Solid or Rubber Ride	Solid or Rubber Ride	Rubber Ride	Rubber Ride	---
Electric Brakes	Optional	Standard	Standard	Standard	---
Front Steering Axle	---	---	Optional	Standard	---
Hitch Type	Ball Coupler or Lunette Eye	Ball Coupler or Lunette Eye	Ball Coupler or Lunette Eye	Ball Coupler or Lunette Eye	---
Adjustable Length Pole Hitch	---	---	Optional	Standard	---
Jack Type	Top Wind	Top Wind	Top Wind	Top Wind	---
Tires	ST225/75R15 Radial	ST235/85R16 Radial	ST235/85R16 Radial	ST235/85R16 Radial	---
Curb Weight (approx.)	860 lb				---

All models have LED Lights as standard features.

