



TRANSPORT SERIES

THE TRANSPORT SPECIALISTS

Loading and transporting your straight cut headers is now easy and simple. Whether traveling long distances or simply moving your equipment around the farm, these transports are built to last.



SPECIFICATIONS

Features	HT6000	HT7000	HTM	HT21000SB
Main Frame	8" x 6" Structural Tubing	8" x 6" Structural Tubing	8" x 8" Structural Tubing	Dual 8" x 6" Structural Tubing
Length	29.5'	38'	---	---
Header Brackets	Dual Arms	Quad Adjustable Arms	Quad Adjustable Arms	Slanted Bed
Axle(s)	Single 6000 lb	Single 7000 lb	Single and Tandem	Tridem
Suspension	Solid or Rubber Ride	Solid or Rubber Ride	Rubber Ride	Rubber Ride
Electric Brakes	Optional	Standard	Standard	Standard
Front Steering Axle	---	---	Optional	Standard
Hitch Type	Ball Coupler or Lunette Eye	Ball Coupler or Lunette Eye	Ball Coupler or Lunette Eye	Ball Coupler or Lunette Eye
Adjustable Length Pole Hitch	---	---	Optional	Standard
Jack Type	Top Wind	Top Wind	Top Wind	Top Wind
Tires	ST225/75R15 Radial	ST235/85R16 Radial	ST235/85R16 Radial	ST235/85R16 Radial
Curb Weight (approx.)	860 lb			

All models have LED Lights as standard features.



Trailtech Inc.
Box 988
Gravelbourg, Saskatchewan
Canada S0H 1X0