### **Harvester Series**

Models: CT220TT, CT220PH, CT3200





## **Transport Series**

Models: SR6000, SR18000T, ST2000, DR21000

Loading and transporting your straight cut headers and swathers is now easy and simple. Whether traveling long distances or simply moving your equipment around the farm, these transports are built to last. The Model SR6000HT is designed for a single rigid header, the SR18000T has been designed to transport draper, flex, corn or pick up headers while the DR21000 is a hydraulic fold-up transport that can carry two headers. The Model ST2000 is a full carry swather transport.



Model: SR6000



Model: SR18000T



Model: DR21000



Model: ST2000

## **Harvester Series**







Model: CT220PH Model: CT3200

#### **Harvester Series Specifications**

Features	CT220TT	CT220PH	CT3200	
Main Frame	12″ I-beam	12″ I-beam	T1 Fabricated beam	
Crossmembers	Structural tubing	Structural tubing	Structural tubing	
Axles	(2) 22,500 lb Dual, 10 Bolt outboard hub piloted axles	(2) 22,500 lb Dual, 10 Bolt outboard hub piloted axles	(3) 22,500 lb, 10 Bolt outboard hub piloted axles	
Suspension	Spring	Spring	Spring	
Air Brakes c/w Anti-lock Braking System	Standard	Standard	Standard	
Level Load Carrying Bed	Standard	Standard	Standard	
Hitch Type	Torque tube fifth wheel	Pintle	Fifth wheel	
Tires	255/70R22.5 Radial	255/70R22.5 Radial	255/70R22.5 Radial	
Curb Weight	11,155 lb	9039 lb	17,960 lb	

<sup>\*</sup> All models have the following standard features: Bi-folding ramps, Closed width of 8.5′, Spring brake chambers, Automatic slack adjusters.

# **Transport Series**









Model: SR6000 Model: SR18000T Model: DR21000 Model: ST2000

#### **Transport Series Specifications**

Features	SR6000	SR18000T	DR21000	ST2000
Main Frame	8" x 6" Structural tubing	8" x 6" Structural tubing	8" x 4" Structural tubing	8" x 2" Tubing
Crossmembers	n/a	Various size tubing	Various size tubing	Various size tubing
Header Brackets	Standard	Full carry bed	Hydraulic folding	n/a
Axle(s)	Single 6000 lb	Tandem 6000 lb	Triple 7000 lb	Tandem 7000 lb
Suspension	Spring or Rubber ride	Rubber ride	Rubber ride	Rubber ride
Electric Brakes	Optional	Standard	Standard	Standard
Front Steering Axle	n/a	Standard	n/a	n/a
Hitch Type	Implement Style	Ball coupler or Lunette eye	Pintle or Gooseneck hitch	Pintle hitch
Adjustable Length Pole Hitch	n/a	Standard	n/a	n/a
Jack Type	Top wind	Top wind	Side crank drop foot	Side crank drop foot
Adjustable Ramps	n/a	n/a	n/a	Standard
Tires	ST225/75R15 Radial	ST225/75R15 Radial	LT235/85R16 Radial	LT235/85R16 Radial
Curb Weight	860 lb	2414 lb	5732 lb	4497 lb